



# DA410<sup>TM</sup>

## Anemometer with Volume Calculation



- ✓ Enter, Store, and Recall up to 10 unique duct sizes
- ✓ High accuracy:  $\pm 1.0\% + 1$  digit of reading
- ✓ Rugged metal probe and vane
- ✓ Intuitive user interface design
- ✓ Ultra low speed sensitivity down to 50 ft/min
- ✓ Industrial grade enclosure and probe
- ✓ Measure airflow in extreme environments from  $-20^{\circ}$  to  $100^{\circ}\text{C}$
- ✓ Protective rubber boot & splash-proof option
- ✓ Minimum and Maximum air volume capture
- ✓ Analog voltage output and USB or RS232 Communication options
- ✓ Selection of velocity sample rates

*The Pacer DA410 Rotating Vane Anemometer is a high quality instrument providing accurate air velocity and volume flow measurements in harsh environments. The user can easily enter the size of the duct opening and the DA410 automatically calculates the volume flow rate from the duct. The duct size is automatically stored in memory on turn-off and up to 10 unique duct sizes can be stored and recalled for frequent use.*

**Pacer Instruments  
by Miltronics Mfg. Svcs., Inc.**  
95 Krif Road  
Keene, New Hampshire 03431 USA  
Email: [sales@pacer-instruments-usa.com](mailto:sales@pacer-instruments-usa.com)  
Phone: 603-352-0187  
Fax: 603-352-1036

Toll Free: 1-800-283-1141  
[www.pacer-instruments-usa.com](http://www.pacer-instruments-usa.com)



**Pacer Calibration and Service  
by Miltronics Mfg. Svcs., Inc.**  
95 Krif Road  
Keene, New Hampshire 03431 USA  
Email: [sales@pacer-instruments-usa.com](mailto:sales@pacer-instruments-usa.com)  
Phone: 603-352-0187  
Fax: 603-352-1036



# DA410™

## Anemometer with Volume Calculation

### SPECIFICATIONS

#### Ranges

Probe AP275: 50 to 7800 FPM (feet per minute)  
0.25 to 40.00 MPS (meters per second)

Probe AP100: 300 to 6890 FPM  
1.5 to 34.50 MPS

Calculated Air Volume Flow:  
0.0 to 9999 ft<sup>3</sup>/min (CFM - cubic feet per minute)  
0.0 to 9999 m<sup>3</sup>/hr (CMH - cubic meters per hour)

#### Accuracy

2.75" Probes: ±1.0% of Reading ±1 digit  
1.00" Probes: ±0.50% F.S. + 0.75% Reading + 1 digit

#### Resolution

1 FPM or 0.01 MPS

#### Display

0.5" LCD, 4 digits, with LED backlight

#### Operating Temp

Instrument: 32° to 125°F / 0° to 50°C  
Probe: -4° to 212°F / -20° to 100°C

#### Power Supply

3 AA alkaline batteries

#### Battery Life

Approximately 150 hours

#### Dimensions

Instrument: 6.5 inch X 3.25 inch X 1.5 inch  
Probe AP275: 2.75 inch diameter  
Probe AP100: 1 inch diameter

#### Instrument Options Available

- Protective Rubber Boot and Splash-Proof Seal
- USB or RS232 communications
- Analog 0-5 Volt output

#### Misc. Options

- Additional Probe PN AP100 or AP275
- Extra extension and/or flexible rods
- Custom cable lengths (Stocked in 5ft increments)

#### DA410 comes complete with

- 1 pc. rotating vane probe head, your choice of AP275 (2.75 inch diameter) or AP100 (1 inch diameter)
- 3 pc. 10" extension rod w/ handle grip
- 1 pc. 10" flexible rod
- 1 pc. 5' connecting cable  
Note: cable attached to AP100 probe
- 3 pc. AA 1.5 V alkaline batteries
- 1 pc. carrying case & manual
- NIST-Traceable Calibration Certificate



**Pacer Instruments**  
by **Miltronics Mfg., Inc.**  
95 Krif Road  
Keene, New Hampshire 03431 USA  
Email: sales@pacer-instruments-usa.com  
Phone: 603-352-0187  
Fax: 603-352-1036

Toll Free: 1-800-283-1141  
www.pacer-instruments-usa.com



**Pacer Calibration and Service**  
by **Miltronics Mfg., Inc.**  
95 Krif Road  
Keene, New Hampshire 03431 USA  
Email: sales@pacer-instruments-usa.com  
Phone: 603-352-0187  
Fax: 603-352-1036